

AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

Page: 1

Compilation date: 21/05/2012

Revision date: 06/04/2022

Revision No: 7

# Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Product name: AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Airborne Disinfectant. For professional use only. Uses advised against: Uses other than the intended use of the product.

#### 1.3. Details of the supplier of the safety data sheet

Company name: Tristel Solutions Limited Lynx Business Park Fordham Road

Newmarket

Cambridgeshire

CB8 7NY

United Kingdom

Tel: +44 (0) 1638 721 500

Fax: +44 (0) 1638 721 911

Email: SDS@tristel.com

## 1.4. Emergency telephone number

Emergency tel: National Poisons Information Service, UK NPIS

# 0344 892 0111

### Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CLP:	Eye Irrit. 2: H319; STOT SE 3: H336; Flam. Aerosol 1: H222; Aquatic Chronic 3: H412; -:	
	H229	
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes	
	serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with	
	long lasting effects.	

## 2.2. Label elements

#### Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

## AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

		. age
	H336: May cause drowsiness or dizziness.	
	H412: Harmful to aquatic life with long lasting effects.	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	
	$\wedge$ $\wedge$	
	$\checkmark$ $\checkmark$	
Signal words:	Danger	
Precautionary statements:	P261: Avoid breathing vapours.	
	P280: Wear protective gloves/protective clothing/eye protection/face protection.	
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition	
	sources. No smoking.	
	P211: Do not spray on an open flame or other ignition source.	
	P251: Do not pierce or burn, even after use.	
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove	
	contact lenses, if present and easy to do. Continue rinsing.	
	P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.	
	P264: Wash hands thoroughly after handling.	
	P273: Avoid release to the environment.	
	P403+P233: Store in a well-ventilated place. Keep container tightly closed.	
	P501: Dispose of contents/container to in accordance with dangerous residues	
	regulations.	
2.3. Other hazards		
Other hazards:	No significant health risks if used under standard conditions of commercial and	
	industrial use. The product is irritating if it comes in contact with eyes, in this case it is	

industrial use. The product is irritating if it comes in contact with eyes, in this case it is recommended to wash immediately, with plenty of water.

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

## Hazardous ingredients:

## PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%

## Section 4: First aid measures

**Page:** 2

## AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

asures
sures
Wash immediately with plenty of soap and water.
Bathe the eye with running water for 15 minutes. Seek medical attention if eye irritation
persists.
Wash out mouth with water. Do not induce vomiting. Consult a doctor.
Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a
doctor.
and effects, both acute and delayed
There may be mild irritation at the site of contact.
There may be irritation and redness.
There may be soreness and redness of the mouth and throat. Inhalation of fumes from
the stomach may cause symptoms similar to direct inhalation.
There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness
or mental confusion may occur.
Immediate effects can be expected after short-term exposure.
e medical attention and special treatment needed
Eye bathing equipment should be available on the premises.
res
Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Water fog. Use water
spray to cool containers.
om the substance or mixture
In combustion emits toxic fumes.
Wear self-contained breathing apparatus. Wear protective clothing to prevent contact
with skin and eyes.
neasures
tective equipment and emergency procedures
Refer to section 8 of SDS for personal protection details. If outside do not approach from
Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Smoking is forbidden.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

## 7.3. Specific end use(s)

Specific end use(s): Airborne Disinfectant. For professional use only.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

#### Hazardous ingredients:

#### PROPAN-2-OL

#### Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3	1250 mg/m3	-	-

### **DNEL/PNEC** Values

DNEL / PNEC No data available.

#### 8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquified gas

Odour: Characteristic odour

Evaporation rate: No data available.

#### AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

Oxidising:	No data available.		
Solubility in water:	Soluble		
Melting point/range°C:	No data available.	Flammability limits %: lower:	No data available.
upper:	No data available.	Flash point°C:	<23
Part.coeff. n-octanol/water:	No data available.	Autoflammability°C:	No data available.
Vapour pressure:	No data available.	Relative density:	0.784-0.804g/cc
pH:	6.5-8.5	VOC g/l:	No data available.

9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition.

## 10.5. Incompatible materials

Materials to avoid: Not applicable.

#### **10.6.** Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

### **Toxicity values:**

Route	Species	Test	Value	Units
DERMAL	-	LD50	>2000	mg/kg
ORAL	-	LD50	>2000	mg/kg

Hazardous ingredients:

### AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

### **Page:** 6

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

#### **Relevant hazards for product:**

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

#### Persistence and degradability: Biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: Slightly bioaccumulable.

12.4. Mobility in soil

Mobility: Soluble in water.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

### Other adverse effects: Harmful to aquatic organisms.

## Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

#### AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS (FLAMMABLE)

14.3. Transport hazard class(es)

Transport class: 2.1

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 3

### Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This product has been classified in accordance with CLP regulations and compiled in

accordance with Annex II of REACH.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

# Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H222: Extremely flammable aerosol.
	H225: Highly flammable liquid and vapour.
	H229: Pressurised container: May burst if heated.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H412: Harmful to aquatic life with long lasting effects.

Page: 7

Marine pollutant: Yes

AIRSTEL HIGH LEVEL AIRBORNE DISINFECTANT

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Page: 8